

Project

Date

Product Code

Type

Designer



MADE IN USA


[Click Here](#)

ARTIMA® 38E O-OBM

surface mounted LED PAR 38 accent light

FEATURES

- **Artima 38E O-OBM is an accent light** which has been checked for fit and initial operation with two PAR 38 LED retrofit lamps (supplied by others):
 - KETRA S38; and
 - SORAA PAR38.
- **Fixture is designed for mounting on a 4" octagonal outlet box** (by others).
- **The optical assembly for Artima 38 O-OBM is a matte black cross-baffle** which reduces spill light and controls lamp brightness. This assembly and its setting, are entirely undisturbed by relamping.
- **A flared socket cap and light shield ring prevent any backspash of light onto the ceiling.**
- **Artima 38E O-OBM fixtures provide 385° horizontal rotation and vertical adjustment from 0° to 90°.** Lamp focus can be locked by tightening two collar clamps using a 1/64" hex key.
- **Artima 38E O-OBM fixtures accept one or two of a number of [Optical Accessories](#)** including spread lenses, a beam smoother, color filters and light reduction screens.
- **Standard finish is matte white with a white socket lead**; also available in black and Industrial Silver matte paint finishes.
- **For more information, [click here](#).**



APPLICATIONS



Fixture is suitable for 120-volt electrical service and cULus listed for mounting on a standard 4" octagonal outlet box (by others).

LAMPS BY OTHERS

Edison Price Lighting does not include lamps and does not sell either lamps or their accessories.

DIMMING

For dimming compatibility consult the lamp manufacturer's website.

WIRELESS LIMITATIONS

The wireless range of lamped fixtures will vary with lamp and site conditions.

PRODUCT CODE

Complete Product Code..... ART 38 O-OBM
standard finish: matte white with white socket lead

OPTIONS

Specify by adding to the product code.

- matte black housing finish**
black socket lead standard – BLK
- Industrial Silver housing finish**
black socket lead standard – SIL
- custom color paint housing finish**
specify white or black socket lead – WSLV or – BSLV
and identify color in specification CCH

OPTICAL ACCESSORIES

Specify as separate line items.

All are 4 3/4" (121mm) dia. Lenses and filters are glass; screens are aluminum.

- 30° spread lens** LENS/4.75-30
- 30° Daylight Blue spread lens** DAY LENS/4.75-30
- 20° x 55° spread lens** LENS/4.75
- 55° Daylight Blue spread lens** DAY LENS/4.75
- 70° spread lens** LENS/4.75-70
- prismatic lens (Solite)** PLS/4.75
- 40° x 70° spread lens** LENS/4.75-4070
- beam smoother** CLR/4.75
- color filters**
- Daylight Blue DAY/4.75
- Surprise Pink PNK/4.75
- amber AMB/4.75
- blue BLU/4.75
- green GRN/4.75
- red RED/4.75
- 33% light reduction screen** SCR33/4.75
- 50% light reduction screen** SCR50/4.75



41-50 22ND STREET, LIC NY 11101 TEL 718.685.0700 FAX 718.786.8530 www.epl.com

©Copyright, Edison Price Lighting 2019

®Artima is a registered trademark of Edison Price Lighting

LED 0-327 6:19

ARTIMA 38E O-OBM



For current lamp performance data, consult lamp manufacturer's website.