



AUTOBUS®-120 RR DESIGN NOTES

1. Minimum #6 gauge 90° C building wire required for 60 amp service.
2. Autobus-120 RR is single circuit busway suitable for 60-amp, 120 volt service.
3. Two standard Feeds are available, each with integral #8 leads:
 - End Feed
 - In Line Feed (which powers track to one side only).
4. Three standard joints are available:
 - L joint, with or without splices to continue circuit through L joint
 - T joint (no splices available)
 - X joint (no splices available).
5. 4' maximum between hangers.
6. Autobus-120 RR is UL listed to power Edison Price Lighting
 - Track fixtures with 60-amp, 120-volt adapters (-1C) and
 - PowerPoint-120 receptacle accessories (see three separate drawings).
7. Made to order only (lengths cannot be cut and feed positions cannot be altered in the field). From your ceiling and electrical plans Edison Price Lighting will prepare shop drawings for your approval.

DESIGNED BY	DATE	EDISON PRICE LIGHTING	41-50 2nd STREET LIC. NY 11101 TEL 718.685.0700 FAX 718.706.1628 EMAIL DESIGN@EPL.COM
DRAWN BY	DATE		
SUBMITTED BY	DATE	AUTOBUS-120 RR	
DATE	DATE		
PROJECT		TYPE	
QTY		REVISION	
ORDER #		SCALE	
DWG SIZE		SHT. OF	
DWG		REV #	

File Name: