



AUTOBUS®-120 R DESIGN NOTES

1. AutoBus-120 R is single circuit busway suitable for 60-amp, 120 volt service.
2. Two standard Feeds are available, each with integral #8 leads:
 - End Feed
 - In Line Feed (which powers track to one side only).
3. Three standard Joints are available:
 - L Joint, with or without splices to continue circuit through L Joint
 - T Joint (no splices available)
 - X Joint (no splices available).
4. 4' maximum between hangers.
5. AutoBus-120 R is UL listed to power Edison Price Lighting
 - track fixtures with 60-amp, 120-volt adapters (-1C) and
 - PowerPoint-120 receptacle accessories (see three separate drawings).
6. Made to order only (lengths cannot be cut and feed positions cannot be altered in the field). From your ceiling and electrical plans Edison Price Lighting will prepare shop drawings for your approval.

DESIGNED BY	DATE	 41-50 22nd STREET LIC, NY 11101 TEL 718.685.0700 FAX 718.706.1628 E-MAIL DESIGN@EPL.COM
DRAWN BY	DATE	
SUBMITTED BY	DATE	
PROJECT		AUTOBUS-120 R
TYPE	REVISION	SCALE
QTY	ORDER #	BOM #
	DWG.SIZE	SHT. OF
		DWG